



Mini Power Meter—OT-2500

Power Meter

The FTTX Wide Band Mini Power Meter, OT-2500, is a powerful optical measuring tool which can be used in various optical fiber systems and applications, especially in FTTX field installation and maintenance. With 850, 1310, 1490, 1550 nm calibration wavelength, it is ideal for both single mode and multimode fiber field installation and maintenance.

Main Features

- Wide band calibrated wavelength with 850, 1310, 1490 and 1550 nm.
- Ideal for both single-mode and multi-mode optical fibers
- Mini size and easy to use, ideal for field application
- Battery-low and auto-off function for saving battery
- Ergonomic, eye-catching handheld package.
- Backlight LCD display

Applications

- FTTX field installation and maintenance
- Fiber insertion loss measurement
- Fiber attenuation measurement
- Fiber network optic power measurement



Frederick Engineering, Inc.
832 Oregon Avenue, Suite M
Linthicum, MD 21090



Phone: 410-789-7890
Fax: 410-789-7670
e-Mail: fe@fetest.com

www.fetest.com



Specifications

Item/Model	OT-2500
Sensor Type	InGaAs
Wavelength Range	800 to 1800 nm
Power Range	+25 to -50 dBm
Uncertainty	±0.2 dB (or ±5%) at -20 dBm
Resolution	0.01 dB
Linearity	±0.05 dB
Optical Connector	SC*
Unit	dBm
Calibrated Wavelength	850, 1310, 1490, 1550 nm

Size:	120 mm (L) x 60 mm (W) x 25 mm (H)
Weight:	200 g
Battery Power :	15 hours (typical) ¾ Power meter operation.
Temperature:	Operation: 0 to + 50 °C Storage: -20 to + 60 °C
Humidity:	0 to 85% RH (Non-condensing)

Frederick Engineering, Inc.
832 Oregon Avenue, Suite M
Linthicum, MD 21090



www.fetest.com

Phone: 410-789-7890
Fax: 410-789-7670
e-Mail: fe@fetest.com